

US009636147B2

(12) United States Patent

(54) SCREW ASSEMBLY WITH DEFORMABLE BUSHING

(71) Applicant: Alphatec Spine, Inc., Carlsbad, CA

(08)

(72) Inventor: Jens Peter Timm, Carlsbad, CA (US)

(73) Assignee: Alphatec Spine, Inc., Carlsbad, CA

(US

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 227 days.

(21) Appl. No.: 14/713,826

(22) Filed: May 15, 2015

(65) Prior Publication Data

US 2015/0289907 A1 Oct. 15, 2015

Related U.S. Application Data

- (62) Division of application No. 13/420,012, filed on Mar. 14, 2012, now Pat. No. 9,060,812.
- (60) Provisional application No. 61/468,744, filed on Mar. 29, 2011.
- (51) **Int. Cl. A61B 17/70** (2006.01)

(10) Patent No.: US 9,636,147 B2

(45) **Date of Patent:** May 2, 2017

(52) U.S. Cl.

CPC **A61B** 17/7037 (2013.01); **A61B** 17/7002 (2013.01); **A61B** 17/7032 (2013.01); **A61B** 17/7034 (2013.01); **A61B** 17/7035 (2013.01)

(58) Field of Classification Search

CPC A61B 17/7032; A61B 17/7034; A61B 17/7035; A61B 17/7037

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

7,896,902 B2* 3/2011 Jeon A61B 17/7032 606/246

* cited by examiner

Primary Examiner - Nicholas Woodall

(74) Attorney, Agent, or Firm — Dinsmore & Shohl LLP

(57) ABSTRACT

A method of securing a fixation rod to a screw assembly that includes a screw, a bushing, and a receiver includes the steps of inserting the fixation rod within a receiver portion of the bushing and the receiver, advancing a locking member into contact with an engagement surface on a proximal portion of the bushing, applying a force with the locking member to increase an amount of friction between a distal engagement surface of the bushing and a head portion of the screw, and increasing the force to deform a deformable portion of the bushing and increase an amount of friction between the fixation rod and the bushing.

18 Claims, 3 Drawing Sheets

